

Curve Recessed Fixed 96mm fixed LED downlight Origin



Overview

A circular fixed LED downlight with the LED set back within the bezel to reduce glare


IP54 as standard with optional upgrade to IP65.

Finishes

Available in a range of standard and bespoke finish options for the whole luminaire. The standard white bezel is RAL9010 fine texture with 20% gloss, however we can offer any other RAL colour (additional charges and setup charges may apply).

Installation Notes

- Cut hole in ceiling as per cut-out in diagram.
- Wire luminaire cable to Orluna certified driver, ensuring correct polarity (red to positive terminal [+] and black to negative terminal [-]).
- With mains supply switched off, connect driver to mains supply (to avoid damaging the luminaire, do not hot-wire).
- Feed luminaire into cut-out by rotating clockwise pulling the light fitting fully up into the ceiling, ensuring Ø250mm around luminaire and driver is left clear of insulation.



Unit height increases by 21.65mm / 0.85in for Spot and Elliptical beams.

Note: minimum 10mm void required above fitting.

Fixing Method

Min Ceiling Thickness
Max Ceiling Thickness
Max Driver Distance

Trap Springs

5mm
28mm
20m

Driver Options

Non-dim driver
Mains dimming driver
0-10v dimming driver
DALI driver

Fitting Options

60 Minute Fire Rating
Anti-glare Honeycomb Louvre
Sea & Spa
Frosted Lens

LED Colour Temperature

2700K (very warm white)
2938K (warm white)
4000K (by request only)

IP Rating

IP54 as standard.
Optional IP65

50,000 hours to L90 and a 5 year fitting warranty.
Designed and made in the UK.



Unit 9, Severfield Close, Thirsk Industrial Park, THIRSK, YO7 3BX
www.brilliantlighting.co.uk
01845 525664

Curve Recessed Fixed 96mm fixed LED downlight Origin

Origin Engine for superior light

When you've created a beautiful space, you want to faithfully enhance every shade within it. The Origin family of downlights, uplights, spots and linear lights all use a bespoke phosphor LED, which gives exceptionally high colour rendering and the best red rendering worldwide (CRI: 98 & R9: 99). Reds are highly important in accurate representation of many colours, including true whites, so the Origin makes colours look as beautiful as intended.

Origin is also the only core downlight which has ten precise beam angles, so it's adaptable to every setting, gives more control, and allows you to add more drama.

2700K

	Spot			Soft				Speciality		
	<i>Ultra</i>	<i>Spot</i>	<i>Narrow</i>	<i>Medium</i>	<i>Wide</i>	<i>Flood</i>	<i>Wash</i>	<i>Crisp</i>	<i>Elliptical</i>	<i>Elliptical</i>
Beam Width	8°	10°	14°	26°	40°	47°	54°	36°	10x45°	20x40°
Initial Lumens	526	893	1164	1164	1164	1164	1164	1164	893	893
Engine Lumens	183	295	380	975	968	935	942	970	323	320
Engine Lm/W	23	24	33	81	82	79	79	83	31	31

Voltage	36V	36V	34V				36V			
Drive Current	180mA	300mA	300mA				300mA			
Circuit Power (typ)	7.8W	12.2W	11.4W				12.2W			

3000K

	Spot			Soft				Speciality		
	<i>Ultra</i>	<i>Spot</i>	<i>Narrow</i>	<i>Medium</i>	<i>Wide</i>	<i>Flood</i>	<i>Wash</i>	<i>Crisp</i>	<i>Elliptical</i>	<i>Elliptical</i>
Beam Width	9°	10°	14°	27°	41°	47°	55°	36°	10x45°	20x40°
Initial Lumens	561	935	1252	1252	1252	1252	1252	1252	935	935
Engine Lumens	204	302	407	1013	1026	999	1013	1025	350	354
Engine Lm/W	26	25	36	88	87	84	84	88	27	29

Voltage	36V	36V	34V				36V			
Drive Current	180mA	300mA	300mA				300mA			
Circuit Power (typ)	7.8W	12.2W	11.4W				12.2W			

